



SHELTER STRUCTURES AMERICA

PRODUCT SPECIFICATIONS

SHELTER BLAST TENT SERIES

TENT SPECIFICATIONS

Model	L20
Span Width	20m
Eave Height	6.40m
Ridge Height	7.25m
Bay Distance	5m
Roof Pitch	18°
Longest Component	10.70m
Maximum Length	Unlimited in 5-meter increments
Max. Windload	150mph

FRAMEWORK

Main Profiles	120*300*5mm (4 channel)
Material	Hard Pressed Extruded Structural Aluminum 6061/T6

COVER

Material	PVC Coated Polyester Fabric
Features	650 or 850 g/sqm, Premium Grade, High Gloss White or Translucent, Waterproof, UV Resistant
Flame Retardant	DIN 4102 B1, M2; USA NFPA701

CONNECTING COMPONENTS

Hot Dipped, Structural Grade Corrosive Resistant Galvanized Steel


BLAST TENT DRAWING

Rendering




Gable Distance: 2.5m

Gable Drawing



Frame Drawing



Profile Specifications

Upright Support Roof Beam ①	Gable Middle Upright ②	Gable Upright ③	Eave Purlin ④
			Roof Purlin ⑤



SHELTER STRUCTURES
TENT MANUFACTURER

Shelter Structures America Inc.

405 Via Chico Suite 1 Palos Verdes Estates, CA 90274

E: robert@shelterstructuresamerica.com

C: (954) 559 8759

W: www.shelterstructuresamerica.com

O: (424) 254 9172