



SHELTER STRUCTURES AMERICA

PRODUCT SPECIFICATIONS

SHELTER THERMO SERIES

TENT SPECIFICATIONS

Model	F10	F15	F20	F25
Span Width	10m	15m	20m	25m
Eave Height	4.00m			
Ridge Height	4.67m	5.07m	5.07m	2.10m
Bay Distance	5.00m			
Roof Pitch	5°			
Longest Component	6.00m	8.10m	10.70m	10.70m
Maximum Length	Unlimited in 5-meter increment			
Max. Windload	115mph			

FRAMEWORK

Main Profiles	112x203x4mm, 120x200x4mm, 120x250x4mm
Material	Hard Pressed Extruded Structural Aluminum 6061/T6

COVER

Material	PVC Coated Polyester Fabric
Features	650 or 850 g/sqm, Premium Grade, High Gloss White or Translucent, Waterproof, UV Resistant
Flame Retardant	DIN 4102 B1, M2; USA NFPA701

CONNECTING COMPONENTS

Hot Dipped, Structural Grade Corrosive Resistant Galvanized Steel

THERMO SERIES DRAWING

F010005



F015005



F020005



F025005



SHELTER STRUCTURES
TENT MANUFACTURER

Shelter Structures America Inc.

405 Via Chico Suite 1 Palos Verdes Estates, CA 90274

E: robert@shelterstructuresamerica.com

C: (954) 559 8759

W: www.shelterstructuresamerica.com

O: (424) 254 9172